

Brute Blast Penetrant-Lubricant

MSDS Number: 82884 - Aerosol

Revision Date: 7/17/06

Page 1 of 5

PRODUCT AND COMPANY IDENTIFICATION

Product Name:

Brute Blast Penetrant-Lubricant

Revision Date:

7/17/06

MSDS Number:

82884 - Aerosol

Product Code:

82884

Manufactured for:

Parts Associates, Inc. 12420 Plaza Dr.

Cleveland, OH 44130

(800) 321-1128 (216) 433-9051 fax www.pai-net.com

COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients:

Cas #	Chemical Name	Perç.
AA**3T4AA	Solvent naphtha, petroleum, heavy arom.** Distillates, petroleum, hydrotreated lig Distillates, petroleum, solvent-dewaxed Alcohols, C11-15-secondary, ethoxylated Carbon dioxide (propellant)	40-50% 30-40% 20-30% 0-3% 0-3%

^{**} solvent naptha contains 1-7% Napthalene (91~20-3) and 0-1% Pseudocumene (95-63-6)

HAZARDS IDENTIFICATION

Route of Entry:

Eyes, skin, inhalation, ingestion

Target Organs:

Inhalation:

Inhalation of spray mist may cause irritation to the respiratory tract.

Skin Contact:

Repeated or prolonged contact with skin may cause mild irritation and possibly dermatitis.

Eye Contact:

Likely to cause immediate or delayed irritation. Irritation will show as redness and/or swelling of the

Ingestion:

Ingestion may cause irritation to the mouth, esophagus and stomach.

May aggrevate pre-existing skin and respiratory disorders.

Notice: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.



Brute Blast Penetrant-Lubricant

MSDS Number: 82884 - Aerosol

Revision Date: 7/17/06

Page 2 of 5

4 **FIRST AID MEASURES**

Inhalation:

Remove to fresh air. If not breathing, give artificial respiration, if breathing is difficult, give oxygen. Continue

to monitor. Get medical attention.

Skin Contact:

Remove contaminated clothing immediately! Wash skin with soap and water. If irritation develops, seek

medical attention.

Eye Contact:

Flush eye(s) with water for 15 minutes. Get medical attention. If eye irritation persists, obtain medical

treatment.

Ingestion:

6

Do not induce vomiting! Get medical attention immediately!

FIRE FIGHTING MEASURES

Flash point: 155°F ASTM D-56 (TCC)

Extinguishing Media: Dry chemical, carbon dioxide or foam is recommended. Water may be ineffective for extinguishment, but can be useful in minimizing or dispersing vapors, protecting personnel and cooling containers. If containers are not properly cooled they can rupture in the heat of a fire. Avoid spreading burning liquid with water used for cooling purposes.

Unusual Fire & Expolsion Hazards: Level 3 Aerosols - Contents Under Pressure!

ACCIDENTAL RELEASE MEASURES

Leaking aerosol cans should be put into suitable container until the internal pressure has dissipated. Use suitable absorbents to collect liquid product. Consult regulations for the disposal of the container, liquid and absorbents.

7 HANDLING AND STORAGE

Handling Precautions:

Use in accordance with good industrial workplace practices. Avoid unnecessary contact. Wash

thoroughly after handling. Use with good ventilation.

Storage Requirements:

Store in a dry place away from excessive heat. Store containers with lids on and properly

labeled.

Do not store at temperatures above 120 degrees F.

EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: Protective Equipment:

Eye wash stations and emegrency showers should be immediately available.

Eyes and Face: Standard safety glasses with splash shields typically offer adequate protection. Where excessive splashing or spraying is possible, a face shield should be used.

Skin and clothing: Excessive contact should be avoided. Neoprene gloves, boots and aprons will provide adequate protection when contact cannot be avoided. Remove and wash any contaminated clothing immediately. Wash thoroughly after handling.

Respiratory: Good general ventilation should be sufficient to control airborne levels. Maintain airborne concentrations below OSHA established exposure limits of ingredients in Section 2.

Exposure Guidelines/Other: The Blaster Chemical Companies takes no responsibility for determining what measures are required for personal protection in any specific application. This information should be used with discretion.



Brute Blast Penetrant-Lubricant

MSDS Number: 82884 - Aerosol Revision Date: 7/17/06

Page 3 of 5

PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Orange viscous oily

Physical State: Liquid

Odor: Heavy aromatic

pH: Not determined Vapor Pressure: Not determined

Vapor Density: >1 (air = 1)

9

Boiling Point: 352 F

Freezing/Melting Pt.: Not determined

Solubility: nil

Spec Grav./Density: 0.87 (water = 1)

Heat Value: Not determined VOC: Not determined Evap. Rate: <1 (NBA = 1) Bulk Density: Not determined Octanol: Not applicable Molecular Weight; Not determined Particle Size: Not applicable Softening Point: Not applicable Viscosity: Not determined Percent Volatile: Not determined Sat. Vap. Concentrat.; Not determined Molecular Formula: Not determined

10 STABILITY AND REACTIVITY

Stability: This product is stable.

Conditions to avoid: Avoid excessive heat, sources of ingition and excessive water.

Materials to avoid (incompatability): Avoid contact with strong oxidizing agents and strong reducing agents (strong acids

or bases.) Avoid mixture with water.

Hazardous Decomposition products: Carbon monoxide, carbon dioxide, and various hydrocarbons.

Hazardous Polymerization: Will not occur.

TOXICOLOGICAL INFORMATION

Toxicological information on this product as a mixture has not been determined. See section 15 for reportable ingredients.

12 **ECOLOGICAL INFORMATION**

Ecological information on this product as a mixture has not been determined.

13 DISPOSAL CONSIDERATIONS

Used or unused product should be disposed of in accordance with local, state, and federal regulations. Some special regulations may exists for the disposal of empty aerosol containers.

Empty containers may contain residual pressure and contents. They should be handled with the same precautions as the product.



Brute Blast Penetrant-Lubricant

MSDS Number: 82884 - Aerosol

Revision Date: 7/17/06

Page 4 of 5

14

TRANSPORT INFORMATION

Dept. of Transportation (DOT):

This product, as it leaves our facilities, meets the definitions set forth in CFR 49 part 173.150c as a "consumer commodity." Allowing for certain exceptions (173.156) for domestic surface (ground) shipments.

Proper shipping name: Consumer Commodity

Hazard class:

ORM-D

International (IMDT-IATA):

Proper shipping name: Aerosols, Limited Quantities **Hazard class:** 2 Flammable Compressed Gas

UN Number:

1950

15

REGULATORY INFORMATION

COMPONENT / (CAS/PERC) / CODES

*Carbon dioxide (propellant) (124389 0-3%) MASS, OSHAWAC, PA, TXAIR

*Distillates, petroleum, solvent-dewaxed heavy paraffinic (64742650 20-30%) NJHS

*Naphthalene (91203 0-1%) CERCLA, CSWHS, EPCRAWPC, HAP, MASS, NJH5, OSHAWAC, PA, PRIPOL, SARA313, TOXICPOL, TOXICRCRA, TXAIR, TXHWL

*Pseudocumene (95636 0-1%) MASS, NJHS, PA, SARA313, TXAIR

REGULATORY KEY DESCRIPTIONS

MASS = MA Massachusetts Hazardous Substances List
OSHAWAC = OSHA Workplace Air Contaminants
PA = PA Right-To-Know List of Hazardous Substances
TXAIR = TX Air Contaminants with Health Effects Screening Level



Brute Blast Penetrant-Lubricant

MSDS Number: 82884 - Aerosol Revision Date: 7/17/06

Page 5 of 5

16

OTHER INFORMATION

Manufacturer's Disclaimer:

To the best of our knowledge, the information contained herein is accurate. However, neither Parts Associates, Inc. nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard which exists.

HMIS Ratings:

Health:

2

NFPA Ratings:

H

Health: 2

Fire: 2 Reacitivity: 0 Fire: 2 Reacitivity: 0

END OF MSDS DOCUMENT