Reviewed on 05/11/2015 Printing date 05/11/2015

1 Identification

· Product identifier

· Trade name: 60000636 G&G MOLY EP 2

· Article number: 09880-2

· Details of the supplier of the safety data sheet

· Manufacturer:

Battenfeld Grease & Oil Corporation of New York

1174 Erie Ave., PO Box 728

NORTH TONAWANDA, NY 14120-0728

info@battenfeld-grease.com

- · Information department: Technical Department
- · Emergency telephone number: During normal opening hours: +1 (716) 695 2100

2 Hazard(s) identification

· Classification of the substance or mixture

The product is not classified according to the Globally Harmonized System (GHS).

- · Label elements
- · GHS label elements Void
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements Void
- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 1Fire = 1Reactivity = 0

· HMIS-ratings (scale 0 - 4)



1 Health = 1Fire = 1

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerous	components:	
8052-42-4	Asphaltic Resin	20-<25%
1317-33-5	molybdenum disulphide	1-2.5%
68457-79-4	Zinc Dialkylthiophosphate	0.1-<1%

Printing date 05/11/2015 Reviewed on 05/11/2015

Trade name: 60000636 G&G MOLY EP 2

(Contd. of page 1)

4 First-aid measures

- · Description of first aid measures
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- · Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

- · Methods and material for containment and cleaning up: Ensure adequate ventilation.
- · Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

(Contd. on page 3)

Reviewed on 05/11/2015 Printing date 05/11/2015

Trade name: 60000636 G&G MOLY EP 2

(Contd. of page 2)

· Control parameters

Control para	
· Components	with limit values that require monitoring at the workplace:
64742-65-0 1	Distillates (petroleum), solvent-dewaxed heavy paraffinic (50-100%)
ACGIH TLV	Long-term value: 5 mg/m³
OSHA PEL	Long-term value: 5 mg/m³
8052-42-4 A	sphaltic Resin (20-<25%)
PEL	Long-term value: 5 mg/m³
REL	Short-term value: 10 mg/m³
	Long-term value: 5 mg/m³
	Ceiling limit value: 5* mg/m³ *15-min; See Pocket Guide App. A
TI V	
TLV	Short-term value: 10 mg/m³ Long-term value: 5 mg/m³
	*inh. fraction; as benzene-soluble aerosol; BEIp
64742 52 5 1	Distillates (petroleum), hydrotreated heavy naphthenic (2.5-<10%)
ACGIH TLV	Short-term value: 10 mg/m ³
	Long-term value: 5 mg/m³
OSHA PEL	Long-term value: 5 mg/m³
1317-33-5 m	olybdenum disulphide (1-2.5%)
PEL	Long-term value: 15* mg/m³
	*Total dust
TLV	Long-term value: 10* 3** mg/m³
	as Mo; *inhalable fraction ** respirable fraction
· Ingredients v	with biological limit values:
8052-42-4 A	sphaltic Resin (20-<25%)

BEI -

Medium: urine

Time: end of shift at end of workweek

Parameter: 1-Hydroxypyrene with hydrolysis (nonquantitative)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

(Contd. on page 4)

Printing date 05/11/2015 Reviewed on 05/11/2015

Trade name: 60000636 G&G MOLY EP 2

(Contd. of page 3)

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· Information on	basic physical	l and chemical	properties
------------------	----------------	----------------	------------

 $\cdot \textit{General Information}$

· Appearance:

Form: Semi-Solid Color: Semy-Solid

• Odor:Petroleum-like• Odour threshold:Not determined.

· pH-value: Not applicable.

· Change in condition

Melting point/Melting range:Undetermined.Boiling point/Boiling range:370 °C (698 °F)

• Flash point: 255 °C (491 °F)

Flammability (solid, gaseous): Not determined.
 Ignition temperature: > 315 °C (> 599 °F)

Ignition temperature: > 315 °C (> 599
 Decomposition temperature: Not determined.

· Auto igniting: Product is not selfigniting.

• Danger of explosion: Product does not present an explosion hazard.

· Explosion limits:

Lower: Not determined. Upper: Not determined.

· Vapor pressure: Not applicable.

• Density at 20 °C (68 °F): 0.94894 g/cm³ (7.919 lbs/gal)

Relative density
 Vapour density
 Evaporation rate
 Not applicable.
 Not applicable.

· Solubility in / Miscibility with

Water: Insoluble.

· Partition coefficient (n-octanol/water): Not determined.

(Contd. on page 5)

Printing date 05/11/2015 Reviewed on 05/11/2015

Trade name: 60000636 G&G MOLY EP 2

		(Contd. of page 4
· Viscosity:		
Dynamic:	Not applicable.	
Kinematic:	Not applicable.	
· Solvent content:		
Organic solvents:	0.0 %	
Solids content:	6.9 %	
· Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

ATE (Acute Toxicity Estimates)

Oral	LD50	34014 mg/kg (rat)
Dermal	LD50	8425 mg/kg (rabbit)
Inhalative	LC50/4 h	59.8 mg/l

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (Inte	ernational 2	Agency for	Research on	Cancer)

8052-42-4 Asphaltic Resin

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

- US

2B

Printing date 05/11/2015 Reviewed on 05/11/2015

Trade name: 60000636 G&G MOLY EP 2

(Contd. of page 5)

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

· UN-Number		
· DOT, ADN, IMDG, IATA	not regulated	
· UN proper shipping name · DOT, ADN, IMDG, IATA	not regulated	
· Transport hazard class(es)	nor regulated	
· DOT, ADN, IMDG, IATA		
· Class	not regulated	
· Packing group		
· DOT, IMDG, IATA	not regulated	
· Environmental hazards:		
· Marine pollutant:	No	
· Special precautions for user	Not applicable.	
· Transport in bulk according to Annex I	II of	
MARPOL73/78 and the IBC Code	Not applicable.	
· UN "Model Regulation":	-	

US -

Printing date 05/11/2015 Reviewed on 05/11/2015

Trade name: 60000636 G&G MOLY EP 2

(Contd. of page 6)

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

68457-79-4 Zinc Dialkylthiophosphate

0.1-<1%

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- · Carcinogenic categories
- · EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

8052-42-4 Asphaltic Resin

A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

8052-42-4 Asphaltic Resin

- · GHS label elements Void
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements Void
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Technical Department
- · Contact: Mr. Wenzler
- · Date of preparation / last revision 05/11/2015 / 4
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

(Contd. on page 8)

Printing date 05/11/2015 Reviewed on 05/11/2015

Trade name: 60000636 G&G MOLY EP 2

 ${\it CAS: Chemical Abstracts Service (division of the American Chemical Society)}$

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

* Data compared to the previous version altered.

(Contd. of page 7)