Safety Data Sheet



Revision Number: 003.0

1. PRODUCT AND COMPANY IDENTIFICATION

Product name:

 Product type:
 Accele

 Restriction of Use:
 None i

 Company address:
 Henkel Corporation

 One Henkel Way
 Rocky Hill, Connecticut 06067

LOCTITE SF 7649 ACTIVATOR known as Loctite(R) Locquic(R) Primer N Accelerator None identified IDH number:


135284

Item number:19266Region:United StatesContact information:Telephone:(860) 571-5100MEDICAL EMERGENCY Phone:Poison Control Center1-877-671-4608 (toll free) or1-303-592-1711TRANSPORT EMERGENCY Phone:CHEMTREC1-800-424-9300 (toll free) or1-703-527-3887Internet:www.henkelna.com

2. HAZARDS IDENTIFICATION

	EMERGENCY OVERVIEW
DANGER:	HIGHLY FLAMMABLE LIQUID AND VAPOR.
	CAUSES SKIN IRRITATION.
	CAUSES SERIOUS EYE IRRITATION.
	MAY CAUSE DROWSINESS OR DIZZINESS.

HAZARD CLASS	HAZARD CATEGORY
FLAMMABLE LIQUID	2
SKIN IRRITATION	2
EYE IRRITATION	2A
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	3



Precautionary Statements

Prevention:	Keep away from heat, sparks, open flames, hot surfaces - no smoking. Keep container tightly closed. No release into water. Use explosion-proof equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing vapors, mist, or spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves, eye protection, and face protection.
Response:	If on skin (or hair): Take off immediately all contaminated clothing. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to remove. Continue rinsing. Call a poison control center or physician if you feel unwell. If skin irritation occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing. In case of fire: Use foam, dry chemical or carbon dioxide to extinguish.
Storage:	Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.
Disposal:	Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Acetone	67-64-1	60 - 100
2-Ethylhexanoic acid	149-57-5	0.1 - 1

* Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

	4. FIRST AID MEASURES
Inhalation:	Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.
Skin contact:	Immediately flush skin with plenty of water (using soap, if available). Remove contaminated clothing and footwear. Wash clothing before reuse. Get medica attention.
Eye contact:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
Ingestion:	DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention.
Symptoms:	See Section 11.
5.	FIRE FIGHTING MEASURES
Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide.
Special firefighting procedures:	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear. In case of fire, keep containers cool with water spray.
Unusual fire or explosion hazards:	Vapors may accumulate in low or confined areas, travel considerable distance to source of ignition, and flash back. Uncontrolled polymerization may occur at high temperatures resulting in explosions or rupture of storage containers.

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Do not allow product to enter sewer or waterways.
Clean-up methods:	Remove all sources of ignition. Evacuate and ventilate spill area; dike spill to prevent entry into water system; wear full protective equipment during clean- up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up as much material as possible. Store in a partly filled, closed container until disposal. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up.

7. HANDLING AND STORAGE

Handling:

Use only with adequate ventilation. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Keep container closed. Refer to Section 8.

Storage:

For safe storage, store at or below 49 °C (120.2 °F) Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER	
Acetone	750 ppm STEL 500 ppm TWA	1,000 ppm (2,400 mg/m3) PEL	None	None	
2-Ethylhexanoic acid	5 mg/m3 TWA Inhalable fraction and vapor.	None	None	None	
Engineering controls:	Provide exposur	adequate local exhaust e limits.	ventilation to maintain v	vorker exposure below	
Respiratory protection:	ion: Use NIOSH approved respirator if there is potential to exceed exposure limit(s).		xceed exposure		
Eye/face protection:	be used	Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Safety showers and eye wash stations should be available.			

Skin protection:

Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact. Neoprene gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES

Liquid

Physical state: Color: Odor: Odor threshold: pH: Vapor pressure: Boiling point/range: Melting point/ range: Specific gravity: Vapor density: Flash point: Flammable/Explosive limits - lower: Flammable/Explosive limits - upper: Autoignition temperature: Evaporation rate: Solubility in water: Partition coefficient (n-octanol/water): **VOC content:** Viscosity: **Decomposition temperature:**

Green Acetone Not available. Not available. 172 mm hg (20 °C (68°F)) 56 °C (132.8 °F) None Not available. 0.7936 2.0 -19 °C (-2.2 °F) ; Estimated 2.6 % 13 % 485 °C (905°F) 1.9 (Ether = 1) Miscible Not available. 1.48 %; 11.7 g/I EPA Method 24 Not available. Not available.

10. STABILITY AND REACTIVITY

Stability:Stable under normal conditions of storage and use.Hazardous reactions:None under normal processing.Hazardous decomposition products:Oxides of nitrogen. Oxides of carbon. Irritating organic vapours.Incompatible materials:Strong oxidizing agents. Reducing agents. Acids. Alkali metals.Reactivity:Not available.Conditions to avoid:Elevated temperatures. Heat, flames, sparks and other sources of ignition. Store away from incompatible materials.		
Hazardous decomposition products: Oxides of nitrogen. Oxides of carbon. Irritating organic vapours. Incompatible materials: Strong oxidizing agents. Reducing agents. Acids. Alkali metals. Reactivity: Not available. Conditions to avoid: Elevated temperatures. Heat, flames, sparks and other sources of ignition. Store away from	Stability:	Stable under normal conditions of storage and use.
products: Incompatible materials: Strong oxidizing agents. Reducing agents. Acids. Alkali metals. Reactivity: Not available. Conditions to avoid: Elevated temperatures. Heat, flames, sparks and other sources of ignition. Store away from	Hazardous reactions:	None under normal processing.
Reactivity: Not available. Conditions to avoid: Elevated temperatures. Heat, flames, sparks and other sources of ignition. Store away from	•	Oxides of nitrogen. Oxides of carbon. Irritating organic vapours.
Conditions to avoid: Elevated temperatures. Heat, flames, sparks and other sources of ignition. Store away from	Incompatible materials:	Strong oxidizing agents. Reducing agents. Acids. Alkali metals.
	Reactivity:	Not available.
	Conditions to avoid:	

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure:	Skin, Inhalation, Eyes, Ingestion

Potential Health Effects/Symptoms

Inhalation: May cause dizziness, incoordination, headache, nausea, and vomiting.	
Skin contact: Causes skin irritation. Solvent action can dry and defat the skin, causing the ski	n to crack,
leading to dermatitis.	
Eye contact: Causes serious eye irritation.	
Ingestion: May cause gastrointestinal tract irritation if swallowed.	

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Acetone	Oral LD50 (RABBIT) = 5,340 mg/kg Oral LD50 (RAT) = 5,800 mg/kg Oral LD50 (RAT) = 9,800 mg/kg Dermal LD50 (RABBIT) = 20,000 mg/kg Inhalation LC50 (RAT, 8 h) = 50.1 mg/l Inhalation LC50 (RAT, 4 h) = 76 mg/l	Blood, Central nervous system, Irritant, Reproductive
2-Ethylhexanoic acid	Oral LD50 (RAT) = 1.6 g/kg Oral LD50 (RABBIT) = 1.3 g/kg Dermal LD50 (RABBIT) = 1,260 mg/kg	Developmental, Eyes, Irritant, Liver, Reproductive

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Acetone	No	No	No
2-Ethylhexanoic acid	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information:

Not available.

13. DISPOSAL CONSIDERATIONS	
Information provided is for unused product only.	
Recommended method of disposal	Follow all local, state, federal and provincial regulations for disposal.
Hazardous waste number:	D001: Ignitable.
14. TRANSPORT INFORMATION	
The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.	
U.S. Department of Transportation G Proper shipping name: Hazard class or division: Identification number: Packing group: International Air Transportation (ICA Proper shipping name: Hazard class or division: Identification number: Packing group: Exceptions:	Acetone 3 UN 1090 II
Water Transportation (IMO/IMDG) Proper shipping name: Hazard class or division: Identification number: Packing group: Exceptions:	ACETONE 3 UN 1090 II Limited quantity (Not more than 1 L). 15. REGULATORY INFORMATION
United States Regulatory Information TSCA 8 (b) Inventory Status: TSCA 12 (b) Export Notification: CERCLA/SARA Section 302 EHS: CERCLA/SARA Section 311/312: CERCLA/SARA Section 313: CERCLA Reportable quantity: California Proposition 65:	All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory. None above reporting de minimis Delayed Health, Immediate Health, Fire None above reporting de minimis Acetone (CAS# 67-64-1) 5,000 lbs. (2,270 kg) This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.
Canada Regulatory Information	

CEPA DSL/NDSL Status:

All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: Sheila Gines, Regulatory Affairs Specialist

Issue date: 08/26/2014

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.